



**Supreme
Heating**

Our Innovation. Your Lifestyle.

HEATSEEKER
NOVAPRO290

FULL INVERTER POOL HEAT PUMP

WITH NATURAL & CLIMATE-FRIENDLY R290 REFRIGERANT





SPIRAL TITANIUM
HEAT EXCHANGER



VARIABLE SPEED
COMPRESSOR



WI-FI ENABLED



ECO FRIENDLY
REFRIGERANT

R290 is a new generation of eco-friendly refrigerants that will not damage the ozone layer if the gas is dissipated into the atmosphere. It also has high thermal performance and large cooling capacity per unit volume.

Combined with high-efficiency titanium heat exchanger and advanced full inverter control, the **NovaPro290** is capable of stable operation in cold weather and extending your swimming season to all year round.

NovaPro290 also can also be installed in limited spaces on the side of the building thanks to the unique air flow and side discharge.

Features:

- R290 Refrigerant
- Space Saving Side Discharge
- Unique Airflow Design
- Full Inverter Technology
- Ultra Silent Operation
- Running Air Temp. -25°C~43°C
- Intelligent Defrosting
- Built-in Wi-Fi for Smart APP Control



MODEL		09	15	18	21	25	28T
PERFORMANCE AT AIR 27°C, WATER 26°C, HUMIDITY 80%							
Heat Capacity	kW	2.60~9.12	4.26~15.15	5.07~18.07	6.05~21.18	7.30~25.11	7.79~28.03
COP		16.25~6.12	16.38~6.15	16.35~6.06	16.35~6.16	16.22~6.05	16.22~6.11
PERFORMANCE AT AIR 15°C, WATER 26°C, HUMIDITY 70%							
Heat Capacity	kW	1.83~6.84	3.09~11.28	4.06~13.33	4.19~14.40	5.04~17.13	5.19~18.53
COP		6.54~4.62	6.43~4.53	6.34~4.48	6.44~4.50	6.38~4.52	6.49~4.57
GENERAL							
Rated input power at air 15°C	kW	0.28~1.48	0.48~2.49	0.64~2.97	0.65~3.20	0.79~3.79	0.80~4.05
Rated input current at air 15°C	A	6.4	10.8	12.9	13.9	16.4	10.2
Circuit Breaker	A	10	15	20	25	30	20
Power Supply		240 H / 50Hz / 1 PH					380 V / 50 Hz / 3 PH
Pool Volume - Cold Climate	Litres	<20,000	<30,000	<40,000	<50,000	<60,000	<80,000
Pool Volume - Warm Climate	Litres	<30,000	<40,000	<50,000	<60,000	<70,000	<100,000
Advised Flow Rate	L/min	70	110	140	160	190	200
Inlet / Outlet	mm	50					
Refrigerant		R290					
Compressor		HIGHLY (Hitachi)					
Casing		Black ABS					
Noise Level (1m)	dBA	34~44.5	38~47.5	38.5~49	39~49.5	40~50	41~51
WEIGHT / DIMENSIONS							
Net Weight	kg	TBA	TBA	TBA	TBA	TBA	TBA
Net Dimensions L x W x H	mm	1000×450×660	1060×450×750		1126×450×800		1175×450×850